

ndx 270 LV

nax PRO LV3601-7 2K wet on wet primer filler & surfacer

nax PRO LV3601-7 is a low VOC, quick-drying two-pack wet on wet primer surfacer & sanding primer filler, with excellent application and sanding properties.

Can be applied wet on wet on sound OEM e-coat with light scuffing & sprayed directly on well prepared plastic parts.

FEATURES & BENEFITS

- · Wet on wet and dry sanding application
- Spectral shade range \$1-7
- Easy application
- Direct application on ED coated panels without sanding







Suitable Substrates

Existing finishes | Steel and Electro-coat (ED) | Glass reinforced laminates nax Pro LV and nax etch primers, plastic primers, epoxy primers and polyester bodyfillers & putties



- 3 Parts nax Pro LV3601/04/07 VHS Primer Surfacer
- 1 Part nax Pro LV360 Hardener
- 0.6-1.2 Parts nax Pro LV5000 Thinners



Spray-gun setup Gravity fed 1.3-1.8 mm

Application pressure:

1.7-2.2 bar 28-30 psi At spray-gun air inlet HVLP max 0.6-0.7 bar (8-10 psi) at the air cap



1 coat for wet on wet

1 - 2 coats for high build

2-3 coats for extra high build



25-35 μ m/coat $50-60 \mu m/coat$ $60-80 \mu m/coat$



Flash off between coats: 5-10min. at 20°C (70°F)

Before 60°C (140°F) baking:

5-10min. at 20°C (70°F)



Dry to recoat (WOW) Dry to sand

20°C (70°F) 30°C (86°F) 30 mins

40°C (100°F) 60°C (100°F) Infra-Red

3 hours

20 mins 2.5 Hours 10 mins 1.5 hours

30 mins 4+8 mins



Final dry sanding P400-P500



Final wet sanding P800-P1000



Re – coating:

nax Premila 8000 Basecoat and nax Premila 7000 2K Topcoat



2004/42/IIB(c)(540)539

The EU limit value for this product (product category: IIB.e) in ready to use form is max 540 g/litre The VOC content of this product in ready to use form is maximum 539



Use suitable respiratory protection

Use air fed mask at all times. Refer to applicable AS/NZS Standards

For detailed information, please refer to the relevant TDS. Visit: nipponpaintautomotive.com.au





DuluxGroup (Australia) Pty Ltd, trading as Dulux Auto Refinish Coatings.